



PX PRO-1VS

Voltage Sensing Portable Wire Feeder (2 Roll)



APPLICATIONS:

- Construction
- Shipbuilding
- Rental fleets
- Manufacturing

PROFAX NO.	INPUT POWER	WIRE DIAMETERS	WIRE FEED SPEED	WEIGHT	DIMENSIONS
PRO-1VS	Open Circuit Voltage & Arc 14-100V DC	.023 - 5/64" (0.6 - 2.0mm)	60 - 800 IPM (1.52 - 20.32 M/MIN)	37 lb. (17 Kg.)	H: 17" (432mm) W: 8½" (216mm) D: 21½" (546mm)

STANDARD FEATURES:

- Trigger hold (reduces operator fatigue on longer welds).
- Two (2) gear driven rolls with Tool-Less roll change. (Uses Miller® style drive rolls).
- .035/.045 solid wire drive rolls included.
- Accepts Miller® style gun connection.
- Digital LED meters
- Top meter can show amperage or wire feed speed.
- CC/CV mode selector switch
- High/Low wire feed speed selector switch
- Wire jog button
- Gas purge button
- Resettable circuit breaker
- 15' Sensor lead with disconnect & Lenco MG-180 clamp
- 3' of 3/0 AWG input cable w/Lenco LC-40HD male connector
- High impact latching case with folding handle & removable legs
- Shielding gas filter

TECHNICAL DATA:

- Power Source Type: CC or CV (DC)
- Weld Circuit Rating: 400A @ 60% duty cycle
- Input Power: Open Circuit Voltage & Arc Voltage
- Spool Capacity: Max. 12"

Processes
MIG (GMAW)
Flux Cored (FCAW)
(Gas & Self Shielded)

3 YEAR WARRANTY

PROFAX NO.	DESCRIPTION
PRO-1VS	Voltage sensing portable wire feeder (2 roll)