



PX200 STICK/TIG WELDING POWER SOURCE



Scan QR code to view demonstration video online.



FEATURES:

- Stick (SMAW) & Lift-Start TIG (GTAW) Welding
- Compact & lightweight design
- Carry handle & shoulder strap make unit easily portable
- Operates on either 115 or 230 Volts AC
- Thermal overload protection
- 12 ft. weld lead with Lenco electrode holder and *Dinse* style connector
- 10 ft. lead with Lenco ground clamp and *Dinse* style connector



230V to 115V Adapter included



SPECIFICATIONS:

- **Processes:** STICK (SMAW) or DC TIG (GTAW)
- **Input Power:** 115/230 Volts AC single phase 50/60 Hz.
- **Output Ratings:**
 - 115V/130 Amp @ 23 VDC/40% Duty Cycle
 - 230V/200 Amp @ 26 VDC/40% Duty Cycle
- **Welding Amperage Range:**
 - 115V/30-130 Amps
 - 230V/30-200 Amps
- **Maximum OCV:** 85
- **Net Weight:** 15.4 lbs. (6 kg)
- **Power Cord:** 10 ft. with 6-50 Plug (240V / 50A)(STD.)

OPTIONAL TIG PACKAGE



- Optional TIG Package (P/N: PX160-TIG KIT) Includes:**
- TIG Torch 150 Amp/12.5'(PX17V-12R)
 - Lenco Connector.....(PX-917-P160)
 - Lenco Gas Hose.....(LGH-96RH)
 - Flowmeter/Regulator.....(PXRf1430-580)
 - TIG Accessory Kit.....(PXAK-2)

SPECIFICATIONS

RATED OUTPUT (% Duty Cycle.)			CURRENT RANGE (A)	OPEN CIRCUIT VOLTAGE (VDC)	INPUT VOLTAGE (VDC) ±10% (50/60 Hz)	INPUT AT RATED LOAD, SINGLE PHASE, 60 Hz			WEIGHT lbs. (kg)	DIMENSIONS mm (in)
40%	60%	100%				A	KVA	KW		
130 A @ 23.2 VDC	110 A @ 22.4 VDC	85 A @ 21.4 VDC	30 - 130	65 - 85	115	43	5.4	3.8	Net: 15.4 lbs. (7 kg) Ship: 24 lbs. (11 kg)	Height: 260 (10.2) Including handle 295 (11.6) Width: 155 (6.1) Length: 430 (16.5)
200 A @ 26 VDC	165 A @ 24.6 VDC	130 A @ 23.2 VDC	30 - 200		230	48	10.9	6.7		

3 YEAR WARRANTY

DUTY CYCLE

